

Fiberoptic Sensor - *Reflectance Dependent**

Model D240







For The Measurement of Distance, Displacement and Vibration of Targets > Ø 6.1 mm

Features

- Reflectance Dependent Output
- 76 mm Total Operating Range
- 0.2 volt/mm Far Side Sensitivity
- Ø 6.1 mm Target Spot Size (0.240 inch)

Tip & Cable Dimensions





FEATURE	mm	inch
Tip Outer Diameter, Ø C	7.92	0.312
Fiberoptic Diameter	6.10	0.240
Tip Length, C	76.2	3.0
Collar Length, B	19.1	0.75
Collar Diameter, Ø B	9.53	0.375
Cable Length, A	914	36
Cable Diameter, Ø A	8.6	0.340
Cable Min. Bend Radius	40	1.6

The output function includes a region of maximum output voltage is referred to as the OPTICAL PEAK. The useable operating range of these devices includes linear ranges on both sides of the peak, as well as operation at the peak itself. Operation in the NEAR SIDE region gives high sensitivity with limited operating range. Operation on the FAR SIDE gives moderate sensitivity with greater operating range.

**These are reflective type transducers based upon detecting the intensity of reflected light. The output is proportional to:*

- *distance between the sensor tip and target; and,*
- *the reflectivity of the target surface.*

D models are commonly used in applications where the target reflectivity stays constant; i.e., the target has a reciprocating or vibratory motion parallel to the axis of the sensor.


AMBIENT LIGHT REJECTION

Incoming light signals are bandpass filtered at a wavelength of 850 ±22 nm.

Analog sensors are fast responding units ideal for process control and vibration measurements in dynamic applications:

- DC-20 KHz bandwidth is standard
- DC-200 KHz or higher (up to 2 MHz) is optional
- DC-100 Hz providing best resolution, is optional

Standard single channel units include amplifier and sensor tip with 914 mm long (3 foot) fiberoptic cable, require +12 VDC input power, and provide 0 to +5 volt analog output with DC - 20 KHz bandwidth.



Standard Enclosure for D Models


CONVERTING THE ANALOG OUTPUT TO DISTANCE

A calibration chart is provided with each sensor giving the voltage output response to distance. There are three ways to derive accurate distance measurements:

a) within the bounds of the linear range, convert the change in voltage output as follows:
Distance = Δ milliVolts ÷ Sensitivity = µm

b) over the non-linear range, create a lookup table using the XY calibration data points, or

c) use a polynomial curve fit to accurately map the sensor's output function



FACTORY CALIBRATIONS


Calibration charts are provided for Near and Far Side regions. A typical factory supplied calibration chart provides:

- Sensor model & serial number
- Date of calibration
- The linear sensing range
- The slope sensitivity
- The y intercept of the linear range
- The AC noise ripple

The XY calibration data points are made available upon request.

END USER CALIBRATION

The effect of changing target reflectance is to shift the voltage output higher or lower. Factory calibrations have the Peak Voltage set to 5.000 volts. A gain control is provided for calibration of the sensor output to various target surfaces. In-situ calibration is performed simply, by adjusting the sensor's tip-to-target gap until the peak output voltage is attained, and then by using the gain control to set the peak voltage to full scale (5.000 volts). After setting the peak to 5 volts, the factory gap calibration chart applies for the target being measured. This procedure allows the sensor to be used to perform precision linear motion measurements on most materials.



Conversions

1 µm = 39.37 µinch
1 mm = 39.37 mils

1 mil = 0.001 inch
1 mil = 25.4 µm
1 mil = 0.0254 mm

Standard Specifications - D240 Far Side


Electronics		Fiberoptics		Analog Output (0-5 Volts)		
Light Source	LED, 850 nm	**Light Beam Spread**	**25°**	**Total Range**	2.4 inch	62 mm
Input Voltage	+12 to +24 VDC	**Tip Material**	300 Series SS	**Linear Range***	0.450 inch	12 mm
Input Current	125 ma max	**Tip Epoxy Outgas**	0.3% @ 200°C 2.4% @ 300°C	**Nominal Standoff***	0.9 inch	22 mm
Bandwidth	DC-20 KHz 3 db down	**Tip Operating Pressure**	15 bar	**Nominal Sensitivity***	5 mv/mil	0.19 volt/mm
Isothermal Drift	0.5%	**Tip Operating Temperature**	-55 to 200°C continuous; to 300°C intermittent 1-2 hours	**Resolution**** **DC - 200 KHz** **DC - 20 KHz** **DC - 100 Hz**	 400 µin 200 µin 100 µin	 10 µm 5 µm 2.5 µm
Operating Temperature	**0 to 70°C**	**Cable Operating Temperature**	**10 to 107°C**			
Weight	**0.8 kg - 1.8 lbs.**	**Cable Jacket**	PVC over Steel Monocoil			

NOTES: *Nominal Standoff = the gap (distance) that places the sensor at the middle of the linear operating range.*

* Standard Specifications provide nominal values only. Actual production values may vary by as much as ±15%.

** These specifications represent best case performance where:
the target is flat, smooth and highly reflective,
the sensor is perpendicular to the target,
the sensor is gapped into its linear range,
fiberoptic cable lengths are standard and the cable is not connectorized,
with dull targets, resolution values can be 2x - 3x higher.

*** for best results, sensors have BNC outputs, not bare wire hookup



FREQUENCY RESPONSE

The standard D sensor has a 20 KHz 2-pole butterworth frequency rolloff. With the 3 db down point set at 20 KHz, the output is flat out to approximately 6 KHz.

PHILTEC, INC., ANNAPOLIS, MD USA 410-757-4404
Fax 410-757-8138 **e-mail sensors@philtec.com**